

# OUTRIGGER PADS

**AlturnaMATS®**

From the Experts in Industrial Safety

Checkers is excited to offer Safety Tech Outrigger Pads!

## SAFETY TECH OUTRIGGER PADS

### FEATURES:

- Safety textured
- Safety orange TuffGrip handles
- No splinters
- No warping
- No delamination
- Lightweight & heavy duty
- Recovery memory after bending
- Engineered to bend but not break!
- Many standard sizes



Safety Texture



**THE ONLY ENGINEERED, QUANTIFIABLE AND RATED OUTRIGGER PAD AVAILABLE TODAY.**

### STANDARD PADS

MODEL	LOAD		WIDTH	LENGTH	HEIGHT	WEIGHT	SQUARE INCH
	VERTICAL	45° ANGLE					
PAD15151.75	40,000 lb. (KG20,412)	18,000 lb. (KG9,072)	15 in. (C38.1)	15 in. (C38.1)	.75 in. (C1.905)	5.5 lb. (KG3.40)	225 (CT1,451.70)
PAD18181	55,000 lb. (KG24,948)	30,000 lb. (KG13,608)	18 in. (C45.72)	18 in. (C45.72)	1 in. (C2.54)	11 lb. (KG4.99)	324 (CT2,090.45)
PAD24241	60,000 lb. (KG27,216)	35,000 lb. (KG15,876)	24 in. (C60.96)	24 in. (C60.96)	1 in. (C2.54)	20 lb. (KG9.07)	576 (CT3,761.35)
PAD24242	62,000 lb. (KG28,123)	40,000 lb. (KG18,144)	24 in. (C60.96)	24 in. (C60.96)	2 in. (C5.08)	38 lb. (KG17.24)	576 (CT3,761.35)

### NON-STOCK SPECIALTY PADS

MODEL	LOAD		WIDTH	LENGTH	HEIGHT	WEIGHT	SQUARE INCH
	VERTICAL	45° ANGLE					
PAD30301	81,000 lb. (KG36,741)	41,000 lb. (KG18,597.6)	30 in. (C76.2)	30 in. (C76.2)	1 in. (C2.54)	31 lb. (KG14.06)	900 (CT5,806.8)
PAD36361	93,000 lb. (KG42,184.8)	43,000 lb. (KG19,504.8)	36 in. (C91.44)	36 in. (C91.44)	1 in. (C2.54)	45 lb. (KG20.41)	1296 (CT8,361.79)
PAD48481	135,000 lb. (KG61,236)	52,000 lb. (KG23,587.2)	48 in. (C121.92)	48 in. (C121.92)	1 in. (C2.54)	80 lb. (KG36.29)	2304 (CT14,865.4)
PAD30302	85,000 lb. (KG38,556)	43,000 lb. (KG19,504.8)	30 in. (C76.2)	30 in. (C76.2)	2 in. (C5.08)	62 lb. (KG28.12)	900 (CT5,806.8)
PAD36362	98,000 lb. (KG44,252.8)	45,000 lb. (KG20,412)	36 in. (C91.44)	36 in. (C91.44)	2 in. (C5.08)	90 lb. (KG40.83)	1296 (CT8,361.79)
PAD48482	140,000 lb. (KG63,504)	55,000 lb. (KG24,948)	48 in. (C121.92)	48 in. (C121.92)	2 in. (C5.08)	160.0 lb. (KG72.58)	2304 (CT14,865.4)

\*8"x10" Outrigger Leg applied under two separate conditions: 10,000# vertically and 10,000# with a 45 degree angle.  
 \*\*TuffGrip Handle located on width side of all pads. Pads 900 sq.in. or larger have two or more handles or more handles opposite each other.  
 \*\*\*Custom size pads available. Requires a minimum order. Lead time for non-stock items is 30-45 days.\*\*\*  
 KEY: C - Centimeters; KG = Kilograms; CT = Square Centimeters



#### NOTICE:

- Foot pads must be smooth and have 80 sq. in. of surface
- Muddy or loose soil conditions may require additional shoring or stacking of pads.
- Excessive flexing and/or bending may shorten the usable life of the pad.
- Acceptable operating temperature range is -40 degrees to 180 degrees F.